

**Röchling**  
**Permal Composites S.A.S.**  
8, Rue André Fruchard  
B.P.12, Maxéville  
54527 LAXOU Cedex/France  
Tel. +33 383 34 24 24  
Fax +33 383 32 23 18  
info@permali.com  
www.permali.com/pallets

**Roechling**  
**Engineering Plastics Pte. Ltd.**  
No. 14 Tuas Avenue 8  
Singapore 639229/Singapore  
Tel. +65 6 863 18 77  
Fax +65 6 863 17 66  
rep@roechling.com.sg  
www.roechling-asia.com

**Röchling**  
**Machined Plastics**  
161 Westec Drive  
Mount Pleasant, PA 15666/USA  
Tel. +1 724 696-5200  
Fax +1 724 696-5300  
www.roechling.biz  
rmp@roechling.biz

**Röchling**  
**Technische Kunststoffe KG**  
Guerickestr. 5  
06686 Lützen/Germany  
Tel. +49 34444 308-0  
Fax +49 34444 308-10  
kontakt@roechling-luetzen.de  
www.roechling-luetzen.de


**Röchling**  
**Engineering Plastics (UK) Ltd.**  
Waterwells Business Park  
Waterwells Drive  
Gloucester GL2 4AA/Great Britain  
Tel. +44 1452 72-7900  
Fax +44 1452 72-8056  
sales@roechling-plastics.co.uk  
www.roechling-plastics.co.uk

**Röchling**  
**Machined Plastics Italia s.r.l.**  
Via Boldrocchi 5/7  
20046 Biassono, Milano/Italy  
Tel. +39 039 2324324  
Fax +39 039 2324331  
compositi@roechling.it  
www.roechling.it

**Roechling**  
**Engineering Plastics (India) Pvt. Ltd.**  
302, A Wing  
Leo, 24th Road  
Khar West, Mumbai - 400 052/India  
Tel. +91 22 2648 22 61 or -62  
Fax +91 22 2648 22 63  
durostone@roechling-india.com

**Roechling**  
**International (Shanghai) Co., Ltd.**  
26/F Shanghai Times Square  
Office Tower,  
93 Huai Hai Zhong Road  
Shanghai 200021/P.R. China  
Tel. +86 21 5117 6360  
Fax +86 21 5117 7963  
ris@roechling-plastics.com.cn  
www.roechling-asia.com






● Durostone® stocking locations



rc/6452/0308/0119/215.1 (GB)

## Durostone® - PCB Solder Pallet Materials

High performance composite materials  
specifically designed for the  
PCB assembly process



Durostone®

Fibre reinforced plastics




## Durostone® PCB Solder Pallet Materials



Durostone® materials have been developed for all procedures within the PCB assembly process. There are three main grades which are suitable for use in the SMT reflow and wave soldering processes, **Durostone® CHP760, CAS761 & CAG762**. These materials offer the following features,


- Excellent mechanical properties at elevated temperatures including the lead-free process.
- Low thermal conductivity.
- Excellent machining properties enabling the manufacture of complex design solder pallets.
- Good resistance to chemicals used in modern fluxes.



**CHP760**

**CAS761**

**CAG762**



## Durostone® Harsh environments




A combination of flux, temperature and process cycles can result in the degradation of the standard Durostone® grades of material.

The solution is **Durostone® CFR767** which has been specifically formulated for use with aggressive fluxes and high process temperatures.

The resin used to produce Durostone® CFR767 can withstand temperatures up to 300°C. The decision to use Durostone® CFR767 over one of the standard grades is made when the solder bath temperature exceeds 265°C and the bottom side PCB pre-heat exceeds 140°C.

Durostone® CFR767 has excellent flux resistance. When fluxes containing halides or dicarboxylic acids are used in high volume production the lifespan of the standard grades of material can be reduced so Durostone® CFR767 is an ideal solution.

**CFR767**







Technical Data		CHP760	CAS761	CAG762	CFR767
<b>Grade</b>		Standard	Anti-Static	Anti-Static Optical	Flux Resistant
<b>Colour</b>		Blue	Black	Grey	Black
<b>Density (g/cm<sup>3</sup>)</b>		1.90	1.90	1.90	1.80
<b>Flexural Strength 3 point support ⊥ (MPa)</b>	@ 23°C	360	360	360	380
	@ 150°C	180	180	180	260
	@ 185°C	–	–	–	150
<b>Modulus of Elasticity (MPa)</b>	@ 23°C	18,000	18,000	18,000	18,000
	@ 150°C	9,000	9,000	9,000	14,000
	@ 185°C	–	–	–	10,000
<b>Water Absorption (%)</b>		< 0.20	< 0.20	< 0.20	< 0.20
<b>Coefficient of Linear Expansion (10<sup>-6</sup>/K) between 30°C &amp; 200°C</b>		13	11	11	11
<b>Thermal Conductivity (W/m<sup>2</sup>K)</b>		0.25	0.25	0.25	0.23
<b>Maximum Operating Temperature (°C) 10 – 20 seconds</b>		300	300	300	380
<b>Standard Operating Temperature (°C)</b>		260	260	260	300
<b>Surface Resistivity (ohms)</b>		–	10 <sup>5</sup> - 10 <sup>8</sup>	10 <sup>5</sup> - 10 <sup>8</sup>	10 <sup>5</sup> - 10 <sup>8</sup>
<b>Chemical Resistance</b>		Good	Good	Good	Excellent
<b>Sheet Size (mm)</b>		2440 x 1220			
<b>Thickness available (mm)</b>		3, 4, 5, 6, 8, 10, 12			5, 6, 8, 10
<b>Thickness Tolerance</b>		± 0.10			
<b>Flatness Tolerance (for a panel size of 300 x 300)</b>		0.20			
<b>Parallelism</b>		0.10			

**Röchling  
Permal Composites S.A.S.**  
8, Rue André Fruchard  
B.P.12, Maxéville  
54527 LAXOU Cedex/France  
Tel. +33 383 34 24 24  
Fax +33 383 32 23 18  
info@permali.com  
www.permali.com/pallets

**Röchling  
Engineering Plastics Pte. Ltd.**  
No. 14 Tuas Avenue 8  
Singapore 639229/Singapore  
Tel. +65 6 863 18 77  
Fax +65 6 863 17 66  
rep@roechling.com.sg  
www.roechling-asia.com

**Röchling  
Machined Plastics**  
161 Westec Drive  
Mount Pleasant, PA 15666/USA  
Tel. +1 724 696-5200  
Fax +1 724 696-5300  
www.roechling.biz  
rmp@roechling.biz

**Röchling  
Technische Kunststoff KG**  
Guerickestr. 5  
06686 Lützen/Germany  
Tel. +49 34444 308-0  
Fax +49 34444 308-10  
kontakt@roechling-luetzen.de  
www.roechling-luetzen.de


**Röchling  
Engineering Plastics (UK) Ltd.**  
Waterwells Business Park  
Waterwells Drive  
Gloucester GL2 4AA/Great Britain  
Tel. +44 1452 72-7900  
Fax +44 1452 72-8056  
sales@roechling-plastics.co.uk  
www.roechling-plastics.co.uk

**Röchling  
Machined Plastics Italia s.r.l.**  
Via Boldrocchi 5/7  
20046 Biassono, Milano/Italy  
Tel. +39 039 2324324  
Fax +39 039 2324331  
compositi@roechling.it  
www.roechling.it

**Röchling  
Engineering Plastics (India) Pvt. Ltd.**  
302, A Wing  
Leo, 24th Road  
Khar West, Mumbai - 400 052/India  
Tel. +91 22 2648 22 61 or -62  
Fax +91 22 2648 22 63  
durostone@roechling-india.com

**Röchling  
International (Shanghai) Co., Ltd.**  
26/F Shanghai Times Square  
Office Tower,  
93 Huai Hai Zhong Road  
Shanghai 200021/P.R. China  
Tel. +86 21 5117 6360  
Fax +86 21 5117 7963  
ris@roechling-plastics.com.cn  
www.roechling-asia.com


● Durostone® stocking locations





## Durostone® – PCB Solder Pallet Materials

High performance composite materials specifically designed for the PCB assembly process



Durostone®

Fibre reinforced plastics

## Durostone® Material Selector

The following flow chart enables the correct choice of material grade depending on the process parameters.

